


EVL SERIES

The right angle equivalent to the VRL series, the EVL provides our customers with an excellent solution when space and clearance are a serious limitation. Helical planetary gears team up with spiral bevel gears to provide a product with robust internal construction, smooth operation and high torque density. 6 arc-min backlash allows the VRL to be applied to a wide range of applications where accuracy and dynamics are in play, but cost is of concern.

The EVL is a solid choice for servo applications in packaging, handling and automation systems. A variety of standard wash down and food grade options are available, making it an attractive option for the toughest environments. We offer the broadest selection of frame sizes and ratios, giving our customers more flexibility than ever before. Industry standard mounting dimensions allow the EVL to be implemented in legacy machine designs, saving our customers valuable time.






EVL SERIES

- Compact, space-saving solution for mid to high end motion control applications
- The widest range of frame sizes and ratios available in the market
- Best-In-class backlash (≤ 6 arc-min)
- Broad range of mounting adapters offer a simple, precise attachment to any motor
- Maintenance-free solution that is lubricated for life. High performance grease allows flexible mounting in any orientation
- Industry standard mounting dimensions
- Assembled in the USA


EVL SERIES Right-angle Planetary

EVL Series Features



- ① Right angle bevel gear configuration allows motor to be mounted at a 90 degree position from the gearbox, saving space
- ② Carburized helical gears with proprietary secondary finishing process for higher accuracy and smooth, quiet operation. 40% higher tooth surface area than the industry standard
- ③ One piece output shaft and planet carrier with two bearings straddling the planet gears. Higher stiffness, torque capacity and safety factor, with guaranteed alignment of gearing
- ④ Uncaged needle roller bearings provide excellent torque density and torsional rigidity. 43% larger bearing surface area compared to the rest of the industry
- ⑤ Optimized mounting system with active centering on motor pilot diameter guarantees alignment of motor. Motor can be installed in any orientation
- ⑥ True concentric motor shaft clamping connection, optimized for your specific motor. Reduced inertia for dynamic performance and balanced for high speed operation
- ⑦ Ring gear machined directly into the housing, not welded or pressed in. Provides greater concentricity and elimination of speed fluctuation

EVL Series Model Code



*1) Motor mounting code varies depending on the motor. Use the selection tool link below to configure the code.

Contact us for additional information or refer to our online gearbox selection tool.
[Selection tool https://www.nidec-drivetechnology.co.jp/selection/all/](https://www.nidec-drivetechnology.co.jp/selection/all/)

The screenshot shows the Nidec Servo Reducer Selection Tool interface, which consists of four main windows:

- Top Left:** Shows the selection flow: "Make a selection from the motor list" (with a "Servo Motor" icon), "Selection flow: Choose motor > Choose series, ratio > Choose frame size > Complete".
- Top Right:** Shows the selection flow: "Make a selection from load condition" (with a "Load Condition" icon), "Selection flow: Series information > Input load condition > Choose frame size > Choose motor > Complete".
- Middle Left:** Shows the selection flow: "Application selection" (with a "Gears" icon), "Selection flow: Choose Application > Input condition > Choose frame size > Choose motor > Complete".
- Middle Right:** Shows the selection flow: "Search reducer model" (with a "Search" icon), "Selection flow: Select reducer model > Selection completed".
- Bottom Right:** A detailed view of the selected "EVS100-E" model. It includes:
 - Reducer model:** EVS100-E
 - Reducer specification:**
 - Duty: Continuous
 - Shaft: Shaft with key
 - Material: Cast iron
 - Shaft diameter: 10 mm
 - Shaft length: 100 mm
 - Shaft center distance: 400 mm
 - Shaft weight: 400 N
 - Attached motor:** AUTOMATION DIRECT
Model: SVL-202
Type: EVL series
 - Motor specification:**
 - Current: 0.1 A
 - Shaft torque: 0.05 Nm
 - Shaft speed: 1000 rpm
 - Shaft power: 0.05 W
 - Shaft torque per unit input speed: 0.005 Nm/rpm
 - Shaft torque per unit output speed: 0.005 Nm/rpm
 - Shaft center distance: 400 mm
 - Shaft weight: 400 N
 - Download dimensions:** PDF, DXF, STEP, IGES, STL, DWG, DAE, STEP, IGES, STL

EVL SERIES Right-angle Planetary

EVL 070 2-Stage Specifications

Frame Size	070									
Ratio	Unit	Note	3	4	5	6	7	8	9	10
Nominal Output Torque	[Nm]	*1	12	16	22	24	24	24	19	19
Maximum Acceleration Torque	[Nm]	*2	29	38	48	54	54	54	38	38
Maximum Torque	[Nm]	*3	33	45	56	63	63	61	45	45
Emergency Stop Torque	[Nm]	*4	50	65	80	90	90	90	65	65
Nominal Input Speed	[rpm]	*5				3300				
Maximum Input Speed	[rpm]	*6				6000				
No Load Running Torque	[Nm]	*7				0.33				
Maximum Radial Load	[N]	*8				1200				
Maximum Axial Load	[N]	*9				1100				
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	0.31	0.27	0.25	0.24	0.23	0.23	0.23	0.23
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.39	0.34	0.32	0.31	0.31	0.31	0.30	0.30
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	0.58	0.53	0.51	0.50	0.50	0.50	0.49	0.49
Efficiency	[%]	*10				93				
Torsional Rigidity	[Nm/arc-min]	*11				3				
Maximum Torsional Backlash	[arc-min]	--				≤ 6				
Noise Level	dB [A]	*12				≤ 80				
Protection Class	--	*13				IP54 (IP65)				
Ambient Temperature	[°C]	--				0-40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*14				1.9				

EVL 070 3-Stage Specifications

Frame Size	070									
Ratio	Unit	Note	15	16	20	25	28	30	35	40
Nominal Output Torque	[Nm]	*1	18	26	26	28	28	19	28	28
Maximum Acceleration Torque	[Nm]	*2	38	54	54	54	54	38	54	54
Maximum Torque	[Nm]	*3	38	54	54	54	54	38	54	54
Emergency Stop Torque	[Nm]	*4	65	90	90	90	90	65	90	90
Nominal Input Speed	[rpm]	*5			3800					
Maximum Input Speed	[rpm]	*6			6000					
No Load Running Torque	[Nm]	*7			0.20					
Maximum Radial Load	[N]	*8			1200					
Maximum Axial Load	[N]	*9			1100					
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	0.073	0.079	0.071	0.071	0.077	0.062	0.070	0.061
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.118	0.124	0.116	0.115	0.122	0.106	0.115	0.106
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Efficiency	[%]	*10				88				
Torsional Rigidity	[Nm/arc-min]	*11				3				
Maximum Torsional Backlash	[arc-min]	--				≤ 9				
Noise Level	dB [A]	*12				≤ 80				
Protection Class	--	*13				IP65				
Ambient Temperature	[°C]	--				0-40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*14				1.7				

EVL 070 3-Stage Specifications

Frame Size	070								
Ratio	Unit	Note	45	50	60	70	80	90	100
Nominal Output Torque	[Nm]	*1	19	28	28	28	28	19	19
Maximum Acceleration Torque	[Nm]	*2	38	54	54	54	54	38	38
Maximum Torque	[Nm]	*3	38	54	54	54	54	38	38
Emergency Stop Torque	[Nm]	*4	65	90	90	90	90	65	65
Nominal Input Speed	[rpm]	*5				3800			
Maximum Input Speed	[rpm]	*6				6000			
No Load Running Torque	[Nm]	*7				0.20			
Maximum Radial Load	[N]	*8				1200			
Maximum Axial Load	[N]	*9				1100			
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	0.070	0.061	0.061	0.061	0.061	0.061	0.061
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.115	0.106	0.106	0.105	0.105	0.105	0.105
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	--	--	--	--	--	--	--
Efficiency	[%]	*10				88			
Torsional Rigidity	[Nm/arc-min]	*11				3			
Maximum Torsional Backlash	[arc-min]	--				≤ 9			
Noise Level	dB [A]	*12				≤ 80			
Protection Class	--	*13				IP54 (IP65)			
Ambient Temperature	[°C]	--				0-40			
Permitted Housing Temperature	[°C]	--				90			
Weight	[kg]	*14				1.7			

*1) At nominal input speed, service life is 20,000 hours

*2) The maximum torque when starting or stopping operation. Apply Cycle Factor f_0 , found on page 468, for higher duty cycle applications

*3) Permitted 10,000 times during service life. Based on 10% of maximum radial load and smooth output shaft

*4) The maximum torque allowed under a stress situation. Permitted 1,000 times during service life

*5) The average input speed at nominal input torque. Maintain housing temperature below permitted value

*6) The maximum intermittent input speed

*7) Torque at no load applied to the input shaft at nominal input speed

*8) The maximum radial load that the gearbox can accept

*9) The maximum axial load that the gearbox can accept

*10) The efficiency at the nominal output torque rating

*11) This does not include lost motion

*12) Contact Nidec Drive Technology for the testing conditions and environment



*13) Various wash-down options are available. Contact Nidec Drive Technology for more details

*14) Weight may vary slightly between models



EVL SERIES Right-angle Planetary

EVL 070 2-Stage Dimensions




Input bore size $\leq \varphi 8\text{ mm}$



Input bore size $\leq \varphi 14\text{ mm}$



Input bore size $\leq \varphi 19\text{ mm}$






Keyed shaft

Smooth shaft

*1) Length will vary depending on motor

*2) Bushing will be inserted to adapt to motor shaft

EVL 070 3-Stage Dimensions



Keyed shaft

Smooth shaft

*1) Length will vary depending on motor

*2) Bushing will be inserted to adapt to motor shaft

EVL SERIES Right-angle Planetary

EVL 090 2-Stage Specifications

Frame Size	090									
Ratio	Unit	Note	3	4	5	6	7	8	9	10
Nominal Output Torque	[Nm]	*1	46	61	67	67	67	74	51	51
Maximum Acceleration Torque	[Nm]	*2	77	105	105	105	105	105	78	78
Maximum Torque	[Nm]	*3	90	121	121	119	119	117	93	93
Emergency Stop Torque	[Nm]	*4	130	170	220	220	220	220	170	170
Nominal Input Speed	[rpm]	*5					3000			
Maximum Input Speed	[rpm]	*6					6000			
No Load Running Torque	[Nm]	*7					1.13			
Maximum Radial Load	[N]	*8					2400			
Maximum Axial Load	[N]	*9					2200			
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	2.12	1.89	1.80	1.76	1.73	1.71	1.70	1.69
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	2.45	2.22	2.13	2.09	2.06	2.04	2.03	2.02
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	4.57	4.35	4.26	4.21	4.18	4.17	4.16	4.15
Efficiency	[%]	*10					93			
Torsional Rigidity	[Nm/arc-min]	*11					10			
Maximum Torsional Backlash	[arc-min]	--					≤ 6			
Noise Level	dB [A]	*12					≤ 80			
Protection Class	--	*13					IP54 (IP65)			
Ambient Temperature	[°C]	--					0-40			
Permitted Housing Temperature	[°C]	--					90			
Weight	[kg]	*14					4.9			

EVL 090 3-Stage Specifications

Frame Size	090									
Ratio	Unit	Note	15	16	20	25	28	30	35	40
Nominal Output Torque	[Nm]	*1	43	66	68	72	78	47	73	78
Maximum Acceleration Torque	[Nm]	*2	77	128	128	128	128	77	128	128
Maximum Torque	[Nm]	*3	77	128	128	128	128	77	128	128
Emergency Stop Torque	[Nm]	*4	170	220	220	220	220	170	220	220
Nominal Input Speed	[rpm]	*5					3300			
Maximum Input Speed	[rpm]	*6					6000			
No Load Running Torque	[Nm]	*7					0.55			
Maximum Radial Load	[N]	*8					2400			
Maximum Axial Load	[N]	*9					2200			
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	0.34	0.38	0.33	0.32	0.37	0.25	0.32	0.25
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.41	0.46	0.40	0.40	0.45	0.33	0.40	0.32
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	0.60	0.65	0.59	0.59	0.64	0.51	0.59	0.51
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Efficiency	[%]	*10					88			
Torsional Rigidity	[Nm/arc-min]	*11					10			
Maximum Torsional Backlash	[arc-min]	--					≤ 9			
Noise Level	dB [A]	*12					≤ 80			
Protection Class	--	*13					IP54 (IP65)			
Ambient Temperature	[°C]	--					0-40			
Permitted Housing Temperature	[°C]	--					90			
Weight	[kg]	*14					4.3			

EVL ogo 3-Stage Specifications

Frame Size	090								
Ratio	Unit	Note	45	50	60	70	80	90	100
Nominal Output Torque	[Nm]	*1	47	73	73	73	78	52	52
Maximum Acceleration Torque	[Nm]	*2	78	128	128	128	128	78	78
Maximum Torque	[Nm]	*3	78	128	128	128	128	78	78
Emergency Stop Torque	[Nm]	*4	170	220	220	220	220	170	170
Nominal Input Speed	[rpm]	*5				3300			
Maximum Input Speed	[rpm]	*6				6000			
No Load Running Torque	[Nm]	*7				0.55			
Maximum Radial Load	[N]	*8				2400			
Maximum Axial Load	[N]	*9				2200			
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	0.32	0.25	0.25	0.25	0.25	0.25	0.25
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.39	0.32	0.32	0.32	0.32	0.32	0.32
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	0.58	0.51	0.51	0.51	0.51	0.51	0.51
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	--	--	--	--	--	--	--
Efficiency	[%]	*10				88			
Torsional Rigidity	[Nm/arc-min]	*11				10			
Maximum Torsional Backlash	[arc-min]	--				≤ 9			
Noise Level	dB [A]	*12				≤ 80			
Protection Class	--	*13				IP54 (IP65)			
Ambient Temperature	[°C]	--				0-40			
Permitted Housing Temperature	[°C]	--				90			
Weight	[kg]	*14				4.3			

*1) At nominal input speed, service life is 20,000 hours

*2) The maximum torque when starting or stopping operation. Apply Cycle Factor f_0 , found on page 468, for higher duty cycle applications

*3) Permitted 10,000 times during service life. Based on 10% of maximum radial load and smooth output shaft

*4) The maximum torque allowed under a stress situation. Permitted 1,000 times during service life

*5) The average input speed at nominal input torque. Maintain housing temperature below permitted value

*6) The maximum intermittent input speed

*7) Torque at no load applied to the input shaft at nominal input speed

*8) The maximum radial load that the gearbox can accept

*9) The maximum axial load that the gearbox can accept

*10) The efficiency at the nominal output torque rating

*11) This does not include lost motion

*12) Contact Nidec Drive Technology for the testing conditions and environment



*13) Various wash-down options are available. Contact Nidec Drive Technology for more details

*14) Weight may vary slightly between models



EVL SERIES Right-angle Planetary

EVL 090 2-Stage Dimensions




Input bore size $\leq \varnothing 14\text{ mm}$



Input bore size $\leq \varnothing 19\text{ mm}$



Input bore size $\leq \varnothing 28\text{ mm}$





*1) Length will vary depending on motor.



*2) Bushing will be inserted to adapt to motor shaft

EVL 090 3-Stage Dimensions




Input bore size $\leq \varnothing 8\text{ mm}$




Input bore size $\leq \varnothing 14\text{ mm}$



Input bore size $\leq \varnothing 19\text{ mm}$



Keyed shaft



Smooth shaft

*1) Length will vary depending on motor.

*2) Bushing will be inserted to adapt to motor shaft

EVL SERIES Right-angle Planetary

EVL 120 2-Stage Specifications

Frame Size	120									
Ratio	Unit	Note	3	4	5	6	7	8	9	10
Nominal Output Torque	[Nm]	*1	77	108	123	154	154	154	128	128
Maximum Acceleration Torque	[Nm]	*2	172	227	272	340	340	340	240	240
Maximum Torque	[Nm]	*3	205	271	325	401	401	401	288	288
Emergency Stop Torque	[Nm]	*4	320	430	500	550	550	550	450	450
Nominal Input Speed	[rpm]	*5				3000				
Maximum Input Speed	[rpm]	*6				6000				
No Load Running Torque	[Nm]	*7				1.88				
Maximum Radial Load	[N]	*8				4300				
Maximum Axial Load	[N]	*9				3900				
Moment of Inertia ($\leq \varnothing 14$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Moment of Inertia ($\leq \varnothing 19$)	[kgcm ²]	--	6.74	5.49	5.02	4.77	4.65	4.55	4.49	4.46
Moment of Inertia ($\leq \varnothing 28$)	[kgcm ²]	--	8.34	7.08	6.61	6.36	6.24	6.14	6.08	6.05
Moment of Inertia ($\leq \varnothing 38$)	[kgcm ²]	--	15.41	14.15	13.69	13.43	13.31	13.22	13.16	13.12
Efficiency	[%]	*10				93				
Torsional Rigidity	[Nm/arc-min]	*11				31				
Maximum Torsional Backlash	[arc-min]	--				≤ 6				
Noise Level	dB [A]	*12				≤ 85				
Protection Class	--	*13				IP54 (IP65)				
Ambient Temperature	[°C]	--				0-40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*14				10.2				

EVL 120 3-Stage Specifications

Frame Size	120									
Ratio	Unit	Note	15	16	20	25	28	30	35	40
Nominal Output Torque	[Nm]	*1	125	136	162	174	174	132	174	172
Maximum Acceleration Torque	[Nm]	*2	229	295	340	340	340	229	340	340
Maximum Torque	[Nm]	*3	229	295	340	340	340	229	340	340
Emergency Stop Torque	[Nm]	*4	450	550	550	550	550	450	550	550
Nominal Input Speed	[rpm]	*5			3100					
Maximum Input Speed	[rpm]	*6			6000					
No Load Running Torque	[Nm]	*7			1.11					
Maximum Radial Load	[N]	*8			4300					
Maximum Axial Load	[N]	*9			3900					
Moment of Inertia ($\leq \varnothing 14$)	[kgcm ²]	--	2.25	2.46	2.20	2.18	2.40	1.87	2.16	1.86
Moment of Inertia ($\leq \varnothing 19$)	[kgcm ²]	--	2.58	2.79	2.53	2.51	2.73	2.20	2.49	2.19
Moment of Inertia ($\leq \varnothing 28$)	[kgcm ²]	--	4.70	4.91	4.65	4.64	4.86	4.33	4.62	4.32
Moment of Inertia ($\leq \varnothing 38$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Efficiency	[%]	*10			88					
Torsional Rigidity	[Nm/arc-min]	*11			31					
Maximum Torsional Backlash	[arc-min]	--			≤ 9					
Noise Level	dB [A]	*12			≤ 85					
Protection Class	--	*13			IP54 (IP65)					
Ambient Temperature	[°C]	--			0-40					
Permitted Housing Temperature	[°C]	--			90					
Weight	[kg]	*14			10					

EVL 120 3-Stage Specifications

Frame Size	120								
Ratio	Unit	Note	45	50	60	70	80	90	100
Nominal Output Torque	[Nm]	*1	132	174	174	174	174	132	132
Maximum Acceleration Torque	[Nm]	*2	240	340	340	340	340	240	240
Maximum Torque	[Nm]	*3	240	340	340	340	340	240	240
Emergency Stop Torque	[Nm]	*4	450	550	550	550	550	450	450
Nominal Input Speed	[rpm]	*5				3100			
Maximum Input Speed	[rpm]	*6				6000			
No Load Running Torque	[Nm]	*7				1.11			
Maximum Radial Load	[N]	*8				4300			
Maximum Axial Load	[N]	*9				3900			
Moment of Inertia ($\leq \varnothing 14$)	[kgcm ²]	--	2.15	1.86	1.85	1.85	1.85	1.85	1.85
Moment of Inertia ($\leq \varnothing 19$)	[kgcm ²]	--	2.48	2.19	2.18	2.18	2.18	2.18	2.18
Moment of Inertia ($\leq \varnothing 28$)	[kgcm ²]	--	4.61	4.31	4.31	4.31	4.31	4.31	4.31
Moment of Inertia ($\leq \varnothing 38$)	[kgcm ²]	--	--	--	--	--	---	--	--
Efficiency	[%]	*10				88			
Torsional Rigidity	[Nm/arc-min]	*11				31			
Maximum Torsional Backlash	[arc-min]	--				≤ 9			
Noise Level	dB [A]	*12				≤ 85			
Protection Class	--	*13				IP54 (IP65)			
Ambient Temperature	[°C]	--				0-40			
Permitted Housing Temperature	[°C]	--				90			
Weight	[kg]	*14				10			

*1) At nominal input speed, service life is 20,000 hours

*2) The maximum torque when starting or stopping operation. Apply Cycle Factor f_0 , found on page 468, for higher duty cycle applications

*3) Permitted 10,000 times during service life. Based on 10% of maximum radial load and smooth output shaft

*4) The maximum torque allowed under a stress situation. Permitted 1,000 times during service life

*5) The average input speed at nominal input torque. Maintain housing temperature below permitted value

*6) The maximum intermittent input speed

*7) Torque at no load applied to the input shaft at nominal input speed

*8) The maximum radial load that the gearbox can accept

*9) The maximum axial load that the gearbox can accept

*10) The efficiency at the nominal output torque rating

*11) This does not include lost motion

*12) Contact Nidec Drive Technology for the testing conditions and environment



*13) Various wash-down options are available. Contact Nidec Drive Technology for more details

*14) Weight may vary slightly between models



EVL SERIES Right-angle Planetary

EVL 120 2-Stage Dimensions




Input bore size $\leq \varnothing 19$ mm




Input bore size $\leq \varnothing 28$ mm



Input bore size $\leq \varnothing 38$ mm



Keyed shaft





Smooth shaft

*1) Length will vary depending on motor



*2) Bushing will be inserted to adapt to motor shaft

EVL 120 3-Stage Dimensions




Input bore size $\leq \varnothing 14\text{ mm}$




Input bore size $\leq \varnothing 19\text{ mm}$



Input bore size $\leq \varnothing 28\text{ mm}$



Keyed shaft



Smooth shaft

*1) Length will vary depending on motor

*2) Bushing will be inserted to adapt to motor shaft

EVL SERIES Right-angle Planetary

EVL 155 2-Stage Specifications

Frame Size	155									
Ratio	Unit	Note	3	4	5	6	7	8	9	10
Nominal Output Torque	[Nm]	*1	132	181	205	266	307	307	233	233
Maximum Acceleration Torque	[Nm]	*2	296	389	458	595	687	687	480	480
Maximum Torque	[Nm]	*3	329	452	531	664	766	766	559	559
Emergency Stop Torque	[Nm]	*4	700	950	1100	1100	1100	1100	750	750
Nominal Input Speed	[rpm]	*5				2000				
Maximum Input Speed	[rpm]	*6				5000				
No Load Running Torque	[Nm]	*7				3.26				
Maximum Radial Load	[N]	*8				9100				
Maximum Axial Load	[N]	*9				8200				
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	23.13	18.57	16.91	16.01	15.58	15.23	14.77	14.66
Moment of Inertia ($\leq \emptyset 38$)	[kgcm ²]	--	27.50	22.94	21.28	20.38	19.95	19.61	19.41	19.03
Moment of Inertia ($\leq \emptyset 48$)	[kgcm ²]	--	40.73	36.17	34.51	33.61	33.18	32.84	32.37	32.26
Efficiency	[%]	*10				93				
Torsional Rigidity	[Nm/arc-min]	*11				60				
Maximum Torsional Backlash	[arc-min]	--				≤ 6				
Noise Level	dB [A]	*12				≤ 85				
Protection Class	--	*13				IP54 (IP65)				
Ambient Temperature	[°C]	--				0-40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*14				19.8				

EVL 155 3-Stage Specifications

Frame Size	155									
Ratio	Unit	Note	15	16	20	25	28	30	35	40
Nominal Output Torque	[Nm]	*1	230	307	316	352	352	240	352	337
Maximum Acceleration Torque	[Nm]	*2	456	687	687	687	687	456	687	687
Maximum Torque	[Nm]	*3	456	687	687	687	687	456	687	687
Emergency Stop Torque	[Nm]	*4	750	1100	1100	1100	1100	750	1100	1100
Nominal Input Speed	[rpm]	*5				2300				
Maximum Input Speed	[rpm]	*6				5000				
No Load Running Torque	[Nm]	*7				2.56				
Maximum Radial Load	[N]	*8				9100				
Maximum Axial Load	[N]	*9				8200				
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	6.40	7.29	6.22	6.15	7.09	4.99	6.09	4.95
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	8.00	8.88	7.81	7.75	8.68	6.58	7.69	6.54
Moment of Inertia ($\leq \emptyset 38$)	[kgcm ²]	--	15.07	15.96	14.89	14.82	15.76	13.66	14.76	13.61
Moment of Inertia ($\leq \emptyset 48$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Efficiency	[%]	*10				88				
Torsional Rigidity	[Nm/arc-min]	*11				60				
Maximum Torsional Backlash	[arc-min]	--				≤ 9				
Noise Level	dB [A]	*12				≤ 85				
Protection Class	--	*13				IP54 (IP65)				
Ambient Temperature	[°C]	--				0-40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*14				20.4				

EVL 155 3-Stage Specifications

Frame Size	155								
Ratio	Unit	Note	45	50	60	70	80	90	100
Nominal Output Torque	[Nm]	*1	240	352	352	352	352	240	240
Maximum Acceleration Torque	[Nm]	*2	480	687	687	687	687	480	480
Maximum Torque	[Nm]	*3	480	687	687	687	687	480	480
Emergency Stop Torque	[Nm]	*4	750	1100	1100	1100	1100	750	750
Nominal Input Speed	[rpm]	*5				2300			
Maximum Input Speed	[rpm]	*6				5000			
No Load Running Torque	[Nm]	*7				2.56			
Maximum Radial Load	[N]	*8				9100			
Maximum Axial Load	[N]	*9				8200			
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	6.07	4.93	4.92	4.91	4.91	4.91	4.91
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	7.66	6.52	6.51	6.51	6.50	6.50	6.50
Moment of Inertia ($\leq \emptyset 38$)	[kgcm ²]	--	14.74	13.59	13.59	13.58	13.58	13.57	13.57
Moment of Inertia ($\leq \emptyset 48$)	[kgcm ²]	--	--	--	--	--	--	--	--
Efficiency	[%]	*10				88			
Torsional Rigidity	[Nm/arc-min]	*11				60			
Maximum Torsional Backlash	[arc-min]	--				≤ 9			
Noise Level	dB [A]	*12				≤ 85			
Protection Class	--	*13				IP54 (IP65)			
Ambient Temperature	[°C]	--				0-40			
Permitted Housing Temperature	[°C]	--				90			
Weight	[kg]	*14				20.4			

*1) At nominal input speed, service life is 20,000 hours

*2) The maximum torque when starting or stopping operation. Apply Cycle Factor f_0 , found on page 468, for higher duty cycle applications

*3) Permitted 10,000 times during service life. Based on 10% of maximum radial load and smooth output shaft

*4) The maximum torque allowed under a stress situation. Permitted 1,000 times during service life

*5) The average input speed at nominal input torque. Maintain housing temperature below permitted value

*6) The maximum intermittent input speed

*7) Torque at no load applied to the input shaft at nominal input speed

*8) The maximum radial load that the gearbox can accept

*9) The maximum axial load that the gearbox can accept

*10) The efficiency at the nominal output torque rating

*11) This does not include lost motion

*12) Contact Nidec Drive Technology for the testing conditions and environment



*13) Various wash-down options are available. Contact Nidec Drive Technology for more details

*14) Weight may vary slightly between models



EVL SERIES Right-angle Planetary

EVL 155 2-Stage Dimensions





Input bore size $\leq \varnothing 28 \text{ mm}$



Input bore size $\leq \varnothing 38 \text{ mm}$











Input bore size $\leq \varnothing 48 \text{ mm}$



*1) Length will vary depending on motor.

*2) Bushing will be inserted to adapt to motor shaft

EVL 155 3-Stage Dimensions

Input bore size $\leq \varphi 19$ mmInput bore size $\leq \varphi 28$ mmInput bore size $\leq \varphi 38$ mm

Keyed shaft

Smooth shaft

*1) Length will vary depending on motor.

*2) Bushing will be inserted to adapt to motor shaft

EVL SERIES Right-angle Planetary

EVL 205 2-Stage Specifications

Frame Size	205									
Ratio	Units	Note	3	4	5	6	7	8	9	10
Nominal Output Torque	[Nm]	*1	421	604	646	646	646	646	478	478
Maximum Acceleration Torque	[Nm]	*2	679	904	1127	1315	1315	1315	931	931
Maximum Torque	[Nm]	*3	750	1064	1327	1498	1498	1498	1144	1144
Emergency Stop Torque	[Nm]	*4	1300	1700	2000	2500	2500	2500	2000	2000
Nominal Input Speed	[rpm]	*5				1500				
Maximum Input Speed	[rpm]	*6				4000				
No Load Running Torque	[Nm]	*7				10.8				
Maximum Radial Load	[N]	*8				15000				
Maximum Axial Load	[N]	*9				14000				
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Moment of Inertia ($\leq \emptyset 38$)	[kgcm ²]	--	93.71	77.72	71.89	68.74	66.43	65.27	64.60	64.28
Moment of Inertia ($\leq \emptyset 48$)	[kgcm ²]	--	128.6	112.6	106.8	103.6	101.3	100.1	99.46	99.14
Moment of Inertia ($\leq \emptyset 65$)	[kgcm ²]	--	214.2	198.2	192.4	189.2	186.9	185.7	185.1	184.7
Efficiency	[%]	*10				93				
Torsional Rigidity	[Nm/arcmin]	*11				175				
Maximum Torsional Backlash	[Arc-min]	--				≤ 8				
Noise Level	dB [A]	*12				≤ 85				
Protection Class	--	*13				IP54 (IP65)				
Ambient Temperature	[°C]	--				0-40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*14				52				

EVL 205 3-Stage Specifications

Frame Size	205									
Ratio	Units	Note	15	16	20	25	28	30	35	40
Nominal Output Torque	[Nm]	*1	442	583	646	683	710	480	710	465
Maximum Acceleration Torque	[Nm]	*2	916	1315	1315	1315	1315	916	1315	1315
Maximum Torque	[Nm]	*3	916	1315	1315	1315	1315	916	1315	1315
Emergency Stop Torque	[Nm]	*4	2000	2500	2500	2500	2500	2000	2500	2500
Nominal Input Speed	[rpm]	*5			2100					
Maximum Input Speed	[rpm]	*6			4000					
No Load Running Torque	[Nm]	*7			4.7					
Maximum Radial Load	[N]	*8			15000					
Maximum Axial Load	[N]	*9			14000					
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	11.49	12.09	11.15	10.98	11.59	10.33	10.83	10.24
Moment of Inertia ($\leq \emptyset 38$)	[kgcm ²]	--	20.28	20.88	19.94	19.77	20.38	19.11	19.62	19.03
Moment of Inertia ($\leq \emptyset 48$)	[kgcm ²]	--	25.10	25.70	24.76	24.59	25.20	23.94	24.44	23.85
Moment of Inertia ($\leq \emptyset 65$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Efficiency	[%]	*10			88					
Torsional Rigidity	[Nm/arcmin]	*11			175					
Maximum Torsional Backlash	[Arc-min]	--			≤ 11					
Noise Level	dB [A]	*12			≤ 85					
Protection Class	--	*13			IP54 (IP65)					
Ambient Temperature	[°C]	--			0-40					
Permitted Housing Temperature	[°C]	--			90					
Weight	[kg]	*14			39					

EVL 205 3-Stage Specifications

Frame Size	205								
Ratio	Units	Note	45	50	60	70	80	90	100
Nominal Output Torque	[Nm]	*1	480	710	710	710	710	480	480
Maximum Acceleration Torque	[Nm]	*2	931	1315	1315	1315	1315	931	931
Maximum Torque	[Nm]	*3	931	1315	1315	1315	1315	931	931
Emergency Stop Torque	[Nm]	*4	2000	2500	2500	2500	2500	2000	2000
Nominal Input Speed	[rpm]	*5				2100			
Maximum Input Speed	[rpm]	*6				4000			
No Load Running Torque	[Nm]	*7				4.7			
Maximum Radial Load	[N]	*8				15000			
Maximum Axial Load	[N]	*9				14000			
Moment of Inertia ($\leq \varnothing 28$)	[kgcm ²]	--	10.76	10.20	10.18	10.16	10.15	10.15	10.14
Moment of Inertia ($\leq \varnothing 38$)	[kgcm ²]	--	19.55	18.99	18.96	18.95	18.94	18.93	18.93
Moment of Inertia ($\leq \varnothing 48$)	[kgcm ²]	--	24.37	23.81	23.78	23.77	23.76	23.75	23.75
Moment of Inertia ($\leq \varnothing 65$)	[kgcm ²]	--	--	--	--	--	--	--	--
Efficiency	[%]	*10				88			
Torsional Rigidity	[Nm/arcmin]	*11				175			
Maximum Torsional Backlash	[Arc-min]	--				≤ 11			
Noise Level	dB [A]	*12				≤ 85			
Protection Class	--	*13				IP54 (IP65)			
Ambient Temperature	[°C]	--				0-40			
Permitted Housing Temperature	[°C]	--				90			
Weight	[kg]	*14				39			

*1) At nominal input speed, service life is 20,000 hours

*2) The maximum torque when starting or stopping operation. Apply Cycle Factor f_0 , found on page 468, for higher duty cycle applications

*3) Permitted 10,000 times during service life. Based on 10% of maximum radial load and smooth output shaft

*4) The maximum torque allowed under a stress situation. Permitted 1,000 times during service life

*5) The average input speed at nominal input torque. Maintain housing temperature below permitted value

*6) The maximum intermittent input speed

*7) Torque at no load applied to the input shaft at nominal input speed

*8) The maximum radial load that the gearbox can accept

*9) The maximum axial load that the gearbox can accept

*10) The efficiency at the nominal output torque rating

*11) This does not include lost motion

*12) Contact Nidec Drive Technology for the testing conditions and environment



*13) Various wash-down options are available. Contact Nidec Drive Technology for more details

*14) Weight may vary slightly between models



EVL SERIES Right-angle Planetary

EVL 205 2-Stage Dimensions





Input bore size $\leq \varnothing 38\text{ mm}$



Input bore size $\leq \varnothing 48\text{ mm}$



Input bore size $\leq \varnothing 65\text{ mm}$



Keyed shaft



Smooth shaft

*1) Length will vary depending on motor.



*2) Bushing will be inserted to adapt to motor shaft

EVL 205 3-Stage Dimensions




Input bore size $\leq \varnothing 28 \text{ mm}$




Input bore size $\leq \varnothing 38 \text{ mm}$



Input bore size $\leq \varnothing 48 \text{ mm}$



Keyed shaft



Smooth shaft

*1) Length will vary depending on motor.

*2) Bushing will be inserted to adapt to motor shaft

EVL SERIES Right-angle Planetary

EVL 235 2-Stage Specifications

Frame Size	235									
Ratio	Units	Note	3	4	5	6	7	8	9	10
Nominal Output Torque	[Nm]	*1	575	765	960	1208	1313	1313	1064	1064
Maximum Acceleration Torque	[Nm]	*2	1160	1555	1945	2112	2112	2063	1812	1529
Maximum Torque	[Nm]	*3	1336	1861	2328	2441	2441	2339	2032	1787
Emergency Stop Torque	[Nm]	*4	2500	3300	4000	4500	4500	4500	3600	3600
Nominal Input Speed	[rpm]	*5				1200				
Maximum Input Speed	[rpm]	*6					3000			
No Load Running Torque	[Nm]	*7					14.5			
Maximum Radial Load	[N]	*8					15000			
Maximum Axial Load	[N]	*9					14000			
Moment of Inertia ($\leq \emptyset 38$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Moment of Inertia ($\leq \emptyset 48$)	[kgcm ²]	--	148.0	122.9	113.3	108.1	104.7	102.7	101.6	101.0
Moment of Inertia ($\leq \emptyset 65$)	[kgcm ²]	--	223.2	198.1	188.6	183.3	180.0	178.0	176.8	176.2
Efficiency	[%]	*10					93			
Torsional Rigidity	[Nm/arcmin]	*11					400			
Maximum Torsional Backlash	[Arc-min]	--					≤ 8			
Noise Level	dB [A]	*12					≤ 85			
Protection Class	--	*13					IP54 (IP65)			
Ambient Temperature	[°C]	--					0-40			
Permitted Housing Temperature	[°C]	--					90			
Weight	[kg]	*14					68			

EVL 235 3-Stage Specifications

Frame Size	235									
Ratio	Units	Note	15	16	20	25	28	30	35	40
Nominal Output Torque	[Nm]	*1	858	1200	1200	1360	1440	948	1440	1440
Maximum Acceleration Torque	[Nm]	*2	1463	2112	2112	2112	2112	1463	2112	2112
Maximum Torque	[Nm]	*3	1463	2112	2112	2112	2112	1463	2112	2112
Emergency Stop Torque	[Nm]	*4	3600	4500	4500	4500	4500	3600	4500	4500
Nominal Input Speed	[rpm]	*5				1500				
Maximum Input Speed	[rpm]	*6					3000			
No Load Running Torque	[Nm]	*7					10.2			
Maximum Radial Load	[N]	*8					15000			
Maximum Axial Load	[N]	*9					14000			
Moment of Inertia ($\leq \emptyset 38$)	[kgcm ²]	--	36.32	37.24	35.75	35.47	36.39	34.39	35.21	34.25
Moment of Inertia ($\leq \emptyset 48$)	[kgcm ²]	--	66.14	67.06	65.57	65.28	66.21	64.21	65.03	64.07
Moment of Inertia ($\leq \emptyset 65$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Efficiency	[%]	*10					88			
Torsional Rigidity	[Nm/arcmin]	*11					400			
Maximum Torsional Backlash	[Arc-min]	--					≤ 11			
Noise Level	dB [A]	*12					≤ 85			
Protection Class	--	*13					IP54 (IP65)			
Ambient Temperature	[°C]	--					0-40			
Permitted Housing Temperature	[°C]	--					90			
Weight	[kg]	*14					70			

EVL 235 3-Stage Specifications

Frame Size	235								
Ratio	Units	Note	45	50	60	70	80	90	100
Nominal Output Torque	[Nm]	*1	948	1440	1440	1440	1440	948	948
Maximum Acceleration Torque	[Nm]	*2	1246	2112	2112	2112	1728	1246	1131
Maximum Torque	[Nm]	*3	1246	2112	2112	2112	1728	1246	1131
Emergency Stop Torque	[Nm]	*4	3600	4500	4500	4500	4500	3600	3600
Nominal Input Speed	[rpm]	*5				1500			
Maximum Input Speed	[rpm]	*6				3000			
No Load Running Torque	[Nm]	*7				10.2			
Maximum Radial Load	[N]	*8				15000			
Maximum Axial Load	[N]	*9				14000			
Moment of Inertia ($\leq \emptyset 38$)	[kgcm ²]	--	35.10	34.18	34.14	34.11	34.10	34.09	34.08
Moment of Inertia ($\leq \emptyset 48$)	[kgcm ²]	--	64.92	63.99	63.95	63.93	63.91	63.90	63.90
Moment of Inertia ($\leq \emptyset 65$)	[kgcm ²]	--	--	--	--	--	--	--	--
Efficiency	[%]	*10				88			
Torsional Rigidity	[Nm/arcm ⁱⁿ]	*11				400			
Maximum Torsional Backlash	[Arc-min]	--				≤ 11			
Noise Level	dB [A]	*12				≤ 85			
Protection Class	--	*13				IP54 (IP65)			
Ambient Temperature	[°C]	--				0-40			
Permitted Housing Temperature	[°C]	--				90			
Weight	[kg]	*14				70			

*1) At nominal input speed, service life is 20,000 hours

*2) The maximum torque when starting or stopping operation. Apply Cycle Factor f_0 , found on page 468, for higher duty cycle applications

*3) Permitted 10,000 times during service life. Based on 10% of maximum radial load and smooth output shaft

*4) The maximum torque allowed under a stress situation. Permitted 1,000 times during service life

*5) The average input speed at nominal input torque. Maintain housing temperature below permitted value

*6) The maximum intermittent input speed

*7) Torque at no load applied to the input shaft at nominal input speed

*8) The maximum radial load that the gearbox can accept

*9) The maximum axial load that the gearbox can accept

*10) The efficiency at the nominal output torque rating

*11) This does not include lost motion

*12) Contact Nidec Drive Technology for the testing conditions and environment



*13) Various wash-down options are available. Contact Nidec Drive Technology for more details

*14) Weight may vary slightly between models




EVL SERIES Right-angle Planetary

EVL 235 2-Stage Dimensions

Input bore size $\leq \varnothing 48 \text{ mm}$



Input bore size $\leq \varnothing 65 \text{ mm}$








Keyed shaft

Smooth shaft


*1) Length will vary depending on motor.

*2) Bushing will be inserted to adapt to motor shaft

EVL 235 3-Stage Dimensions

Input bore size $\leq \varnothing 38$ mm

Keyed shaft



Smooth shaft

*1) Length will vary depending on motor.

*2) Bushing will be inserted to adapt to motor shaft